

Power Silage Grab

The Kerfab Power Silage Grab is built for higher capacity silage handling with larger loaders and telehandlers. It allows operators to lift bigger volumes, clamp securely, and place material accurately during feeding or stacking. It's suited to loading large feed-out carts, moving high volumes in the pit, and stacking silage or bales in the yard. The larger tine and grab profile supports handling bulk material while maintaining control during placement.

Key features at a glance:

- ▶ Larger tine and grab configuration supports handling higher volume silage loads.
- ▶ Range of widths and configurations to suit machine size and workload.
- ▶ Tine spacing is optimised to hold material while limiting spillage.
- ▶ Designed for larger ag loaders and telehandlers in demanding applications.
- ▶ High-capacity hydraulic rams provide strong clamping through dense material.

2 YEAR
STANDARD
WARRANTY

Pivot, pin, and bush arrangements are designed for durability under high-load, high-cycle operation.

Hydraulic system layout provides balanced clamping force and controlled grab movement.

Heavy-duty frame construction is engineered to manage higher load volumes across the full grab width.

Reinforced tine and back frame structure supports load transfer when handling dense silage.

Specifications:

Part Number	Width mm	Bottom Tines	Top Tines
TGS.PO21	2100	9	7
TGS.PO24	2400	11	8



Visit our website